



Redukce svařované EN 10253-4 L=3 (D-d) metrické velikosti

Vyráběné ze svařovaného potrubí nebo svařené z plechů, pro metrické trubky, mořené, dodací podmínky dle DIN 2609. Dostupné v koncentrické (K) a excentrické (E) variantě z materiálu 1.4307 a 1.4404/4432. Na vyžádání s certifikátem EN 10204/ 3.1.



dimenze D/d x s	délka L mm	váha. kg
23/18 x 1,5	15	0,02
28/18 x 1,5	30	0,03
28/23 x 1,5	15	0,02
36/18 x 2,0	51	0,07
36/24 x 2,0	36	0,05
36/29 x 2,0	21	0,03
44/24 x 2,0	60	0,07
44/29 x 2,0	45	0,07
44/34 x 2,0	24	0,05
54/24 x 2,0	90	0,18
54/29 x 2,0	75	0,16
54/34 x 2,0	60	0,13
54/44 x 2,0	30	0,08
69/34 x 2,0	105	0,24
69/44 x 2,0	75	0,20
69/54 x 2,0	45	0,13
84/44 x 2,0	120	0,40
84/54 x 2,0	90	0,30
84/69 x 2,0	45	0,17
104/54 x 2,0	150	0,57
104/69 x 2,0	105	0,44
104/84 x 2,0	60	0,28
129/54 x 2,0	225	1,03
129/69 x 2,0	180	0,90
129/84 x 2,0	135	0,70
129/104 x 2,0	75	0,43
131/86 x 3,0	135	1,05
131/106 x 3,0	75	0,67
154/69 x 2,0	255	1,44
154/84 x 2,0	210	1,22
154/104 x 2,0	150	0,98
154/129 x 2,0	75	0,52
156/86 x 3,0	210	1,93
156/106 x 3,0	150	1,49
156/131 x 3,0	75	0,82

dimenze D/d x s	délka L mm	váha. kg
204/104 x 2,0	300	2,28
204/129 x 2,0	225	1,85
204/154 x 2,0	150	1,33
206/106 x 3,0	300	3,42
206/131 x 3,0	225	2,70
206/156 x 3,0	150	2,00
254/129 x 2,0	375	3,56
254/154 x 2,0	300	3,04
254/204 x 2,0	150	1,71
256/131 x 3,0	375	5,38
256/156 x 3,0	300	4,56
256/206 x 3,0	150	2,57
304/154 x 2,0	450	5,13
304/204 x 2,0	300	3,80
304/254 x 2,0	150	2,09
306/156 x 3,0	450	7,70
306/206 x 3,0	300	5,70
306/256 x 3,0	150	3,14
356/206 x 3,0	450	9,41
356/256 x 3,0	300	6,84
356/306 x 3,0	150	3,71
406/256 x 3,0	450	11,1
406/306 x 3,0	300	7,98
406/356 x 3,0	150	4,28
456/356 x 3,0	300	9,25
456/406 x 3,0	150	4,91
506/306 x 3,0	600	18,8
506/356 x 3,0	450	14,6
506/406 x 3,0	300	10,7
506/456 x 3,0	150	5,50

Další dimenze, materiály a délky na vyžádání.